

Technical Data Sheet

P45GTB-P8717

Copolymer Polypropylene Reinforced with Talcum Powder & Glass Fiber

Nirumand Polymer



Nirumand Polymer Co.
Filled & Reinforced Engineering Plastics

Product Description

P45GTB-P8717 is recycled copolymer polypropylene reinforced with 45% talc and glass fiber offering good mechanical properties, better dimensional stability, good stiffness, good thermal and chemical resistance. This compound is used in automotive industry and other utility products. This grade is designed to be processed in conventional injection molding process.

General Properties

Material Status	•Commercial: Active
Forms	•Pellets
Processing Method	•Injection molding
Color	•Black

Physical Properties	Value	Unit	Test Method
Density	1.3	gr/cm ³	ISO 1183
Melt Mass-flow Rate (MFR) (230°C/2.16 kg)	gr/10 min	ASTM D1238
Shrinkage	%	Internal

Mechanical Properties	Value	Unit	Test Method
Tensile Strength@Yield	40	MPa	ISO 527
Tensile Strength@Break	40	MPa	ISO 527
Elongation @ Break	4	%	ISO 527
Flexural Modulus	4300	MPa	ASTM D790

Impact	Value	Unit	Test Method
Notched Izod Impact (23°C)	> 8	kJ/m ²	ISO 180
Notched charpy Impact (23°C)	kJ/m ²	ISO 179

Hardness	Value	Unit	Test Method
Durometer Hardness	70	Shore D	ASTM D2240

❖ Values shown are average & are not to be considered as product specifications.

Web-site: www.npolymer.com

E-mail: Sales@npolymer.com, Trade@npolymer.com

Address: Abbas abad Industrial Zone-Tehran-Iran

Tel & Fax: (+9821)35000234