

Technical Data Sheet

P20TB-H20-4328/4412

Homopolymer Polypropylene Filled with Talcum Powde

Nirumand Polymer



Nirumand Polymer Co.
Filled & Reinforced Engineering Plastics

Product Description

P20TB-H20-4328/4412 is homopolymer polypropylene filled with 20% talcum powder offering better mechanical properties, dimensional stability, stiffness, good thermal and chemical resistance. This compound is used in appliance industry, automotive applications, electrical goods, housewares and other utility products. This grade is designed to be processed in extrusion techniques.

General Properties

Material Status •Commercial: Active

Forms •Pellets

Processing Method •Extrusion

Color •Black

Physical Properties	Value	Unit	Test Method
Density	1.05	gr/cm ³	ISO 1183
Melt Mass-flow Rate (MFR) (230°C/2.16 kg)	≤ 3	gr/10 min	ASTM D1238
Shrinkage	...	%	Internal
Mechanical Properties	Value	Unit	Test Method
Flexural Modulus	≥ 1600	MPa	ASTM D790
Impact	Value	Unit	Test Method
Notched Izod Impact (23°C)	...	kJ/m ²	ISO 180
Hardness	Value	Unit	Test Method
Durometer Hardness	70	Shore D	ASTM D2240

❖ Values shown are average & are not to be considered as product specifications.

Web-site: www.npolymer.com

E-mail: Sales@npolymer.com, Trade@npolymer.com

Address: Abbas abad Industrial Zone-Tehran-Iran

Tel & Fax: (+9821)35000234